

PHONE IS330.1

ZONE EX 1/21

A professional mobile phone that can be used as a radio with an optional PTT via a programmable key. Thanks to the ISM (Internal Shared Memory) interface, it is also suitable for special MCPTT (Mission Critical Push-To-Talk) communication, allowing the use of other accessories. Thanks to the ISM (internal shared memory) interface, it is also suitable for special MCPTT (Mission Critical Push-To-Talk) communication, which allows the use of other accessories such as RSM (receiver module) or PTT headsets. The Android-based phone is touch-enabled and very easy to manage using MDM (Mobile Device Management).

A powerful battery and the ability to charge using a desktop charger or multi-function charger complete the advantages of this highly durable phone.



Advantages

- Push-To-Talk.
- 13-pin ISM connector (internal shared memory).
- AndroidTM 10.
- For zones 1 and 21.
- Push-To-Talk button (PTT ready, third-party app required, depending on country regulations).
- SOS button for lone worker protection. LWP ready (third-party app required, depending on country regulations).
- Enhanced audio and voice.
- Dual nano SIM.
- Accelerometer, gyroscope, flashlight, light sensor, compass, pressure sensors.

Contents of the set

Phone, battery, i.safe PROTECTOR 2.0 Type C USB cable, universal power adapter, screwdriver, display protection film, quick start guide, and safety instructions.

PHONE IS330.1

ZONE EX 1/21

Technical specifications		
Operating system	Android™ 10	
Processor	SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)	
Memory	4 GB RAM / 64 GB internal memory / microSD memory up to 128 GB	
Frequency	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39	
Dimension	Dimensions: 152.8 x 62 x 26.7 mm / Weight: 318 g	
Display	2.6" Gorilla Glass 3rd generation / 320 x 432 pixels	
Battery	4050 (typ. 4200) mAh, 3.8 V, 14.98 Wh / removable	
Communication	WiFi 2.4 GHz+ 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with up to 8 hotspot connections; Bluetooth 5; GPS, A-GPS; Glonass; Beidou; Galileo; Near Field Communication	
Camera	13 MP AF rear camera / 5 MP FF front camera	
Type of protection	IP68 dust/water resistant / MIL-STD-810G / operating temperature: -44°F to 140°F	
Explosion-proof feature	ATEX: II 2G Ex ib IIC T4 Gb II 2D Ex ib IIIC T135°C Db	IECEx: Ex ib IIC T4 Gb Ex ib IIIC T135°C Db